

# CABLE SAFETY

## Safety Hook

### Description

CableSafe Safety Hooks are used in cable management while conducting maintenance, turnarounds, construction works and industrial works.

The Safety Hook is used as safety product to suspend cables and hoses off the work floor. Employees and contractors use Safety Hooks, which keep the work floor tidy. Safety Hooks are common use and often prescribed in heavy industries such as: oil & gas, refineries, chemical plants, shipyards, electrical and nuclear installations, offshore, maritime and entertainment industries.

Multinationals prescribe the use of CableSafe in company procedures to adhere to the highest safety practices.

### Specifications

**Safety Hook Extreme** designed for use in extreme environments. The extreme Hook is UV stabilized, Flame Retardant and Cold Weather Rated.

The Safety Hook Extreme is marked: UV+FR+COLD.



	6"	9"	9" double	12"	12" double	15"	15" plus
<b>Size cable opening (top)</b>	2.7 cm/1.1"	3.9 cm/1.5"	3.9 cm/1.5"	5.4 cm/2.1"	5.4 cm/2.1"	6.4 cm/2.5"	6.4 cm/2.5"
<b>Size cable opening (bottom/middle)</b>	4.0 cm/1.6"	6.6 cm/2.6"	6.6 cm/2.6"	8.9 cm/3.5"	8.9 cm/3.5"	11.4 cm/4.5"	16.8 cm/6.6"
<b>Maximum Load</b>	40 kg/88 lbs	75 kg/165 lbs	110 kg/242 lbs	190 kg/418 lbs	225 kg/496 lbs	265 kg/584 lbs	275 kg/606 lbs
<b>Weight</b>	40 g/0.09 lbs	103 g/0.23 lbs	160 g/0.35 lbs	292 g/0.64 lbs	460 g/1.01 lbs	518 g/1.14 lbs	560 g/1.23 lbs
<b>Material</b>	Glass reinforced polyester – injection molded product						
<b>Standard Color</b>	● Yellow ● Glow-in-the-dark						
<b>UV</b>	Stabilized, guarantee 10 years - under normal usage conditions						
<b>Flame Retardant</b>	Flame Retardant, UL Recognized, 94V-0 Flame Class Rating (3)						
<b>Cold Fatigue</b>	Protection in cold weather environment						

- > From quantities of >500 pieces (per type) it is possible to engrave the Safety Hook or receive it in a special color. Production time 3 to 4 weeks.
- > Other standard colors are white, black, blue, green and red. Minimum order quantity 500 pieces, price per piece the same as yellow. Production time 3 to 4 weeks.

# CABLE SAFETY

## Safety Hook

### Safety Hook Extreme complies with:

- > 18th Edition IET Wiring Regulations, July 2018.
- > British Standard BS7671:2018, requires cables to be adequately supported against their premature collapse in the event of a fire, January 2019.
- > OSHA Part 1926.150:Subpart F, employer is responsible for the development of a fire protection program to be followed throughout all phases of the construction and demolition work.
- > CPR NEN8012: 2015, creating an obligation to classify cables according to fire behaviour in order to be able to market them in the EU for use in buildings.

MODEL	CHARACTERISTICS
<p><b>Safety Hook</b></p>	<ul style="list-style-type: none"> <li>• Superior quality and last well over 15 years in normal use</li> <li>• Helps with cable management and housekeeping</li> <li>• Easy to use. Cables and hoses are cleared quickly</li> <li>• Seven sizes: 6", 9", 9"double, 12", 12"double, 15" and 15"plus [appr. 15, 23, 36, 30, 49, 39 and 43 cm]</li> <li>• Easily secure loads using a tie-wrap through holes in the hook</li> <li>• Do not conduct electricity or heat</li> <li>• Sold in batches of 25 pieces - minimum order - delivered from stock</li> </ul>

\* All our CableSafe® Safety Hooks have a 3 year warranty

### Specific Models

**Safety Hook Glow-in-the-Dark** proven design helps during power black-outs or emergency situations.

**Safety Hook Black** is designed for the entertainment industries, used in: film studio's, concerts, festivals.

